



SC-718

**Construction Site
Two-way Radio**

VOX Noise Reduction Long Standby Recording Function

Sonice

SC-718

Function Characteristics

- Recording Function
- AI Noise Reduction
- VOX Function
- Emergency Alert
- Long Standby
- Wireless Copy
- One-Key Frequency
- Analog/ Digital Encryption

General Indicator

SPECIFICATION	TRANSMITTER		RECEIVER		
Frequency Range	400-480MHz	Output Power	10W	RF Sensitivity	≤0.25uV / 0.3 uV
Channel Number	16	Current	≤2.6A	Audio Power	≥500mW
Bandwidth	12.5 KHz/25 KHz	Modulation Distortion	<5%(300-3000Hz)	Rated Audio Distortion	≤5%
Operating Voltage	7.4V DC	Max Frequency Deviation	≤8KHz / ≤2.5 KHz	Spurious Rejection	>55dB
Battery Capacity	2600mAh	CTCSS Frequency Deviation	0.75KHz ± 50Hz	Selectivity	>65dB
Operating Temperature	-20°C to +50°C	Remanent Radiation	≤ 7uW	Intermodulation	>60dB
Antenna Impedance	50Ω				
Dimensions	111×59×38mm				

Standard Accessory



Email: info@soniceradio.com

Website: www.soniceradios.com